

# LABEL APPLICATOR AP Series

## APN Series



APN-30



APN-60





APN-100



A Mech-Sensor combines with a sensor that automatically detects labels of different strokes to eliminate the need for manual alignment when you load labels.

- For pre-printed general roll labels. No special (punched or slit) labels or separators required.
- Supports use of label size from 18 x 20mm up to 60 x 100mm.



MODEL	LABEL GAP(mm)	LABEL SIZE(mm)		MAX. OUTSIDE DIAMETER(mm)
		STROKE	WIDTH	
APN-30	2-3	18-60	20-30	100
APN-60		25-60		
APN-100		50-100		

The Mech-Sensor catches the label and automatically detects the stroke for smooth feeding.

## APF Series



APF-30



APF-60




APF-100



A new slidable Mech-Sensor provides support for round, oval, and other non-rectangular labels as well as rectangular labels.

- For eye-catching labels of various shapes that appeal to customers.
- Supports use of the label size from 20 x 20mm up to 60 x 100mm. For pre-printed general roll labels. No special (punched or slit) labels or separators required.



MODEL	LABEL GAP(mm)	LABEL SIZE(mm)		MAX. OUTSIDE DIAMETER(mm)
		STROKE	WIDTH	
APF-30	2-3	20-60	20-30	100
APF-60		20-60		
APF-100		20-100		

Slide The Mech-Sensor to the left or right until it is in the center of the label.

## APN10

APN10-30



The smaller the label it is when you dispense, the more troublesome it becomes.... It assures high performance for small labels.

The new type of a premium tool, APN10-30 assures high performance for small labels.

- For pre-printed general roll labels. No special (punched or slit) labels or separators required.
- Supports use of label size from 10 x 30mm up to 60 x 30mm.

MODEL	LABEL GAP(mm)	LABEL SIZE(mm)		MAX. OUTSIDE DIAMETER(mm)
		STROKE	WIDTH	
APN10-30	2	10-15	20-30	100

### Notice

- Labels must be more than 50µm thick for all models.
- Some types of film, synthetic paper, and other special labels may not be supported.
- Please ask our distributor for details before using special labels.
- We reserve the right to change specifications without prior notice.

© JP PAT. 2708677, 2708680

## TOWA CO.,LTD.

Ginza YK Bldg., #10-9, Ginza 5-chome, Chuo-ku, Tokyo 104-0061, Japan  
Tel: +81-3-3572-9621 Fax: +81-3-3572-9620  
http://www.towa.jp/export/ e-mail: export@towa-ltd.co.jp